

IMAGE PROCESSING METHOD

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to an image processing method and an image processing apparatus used with a printer, a scanner, a duplicator, a facsimile, etc. for reproducing the multivalued image information as a binary image.

Description of the Related Art

The error spreading method is widely known as one of the methods for converting a multivalued image into a binary image.

Fig. 5 is a block diagram showing a conventional circuit for executing the error spreading method.

In Fig. 5, the multivalued data D of an intended pixel to be binarized is read from an image memory 100, and subjected to γ correction into the multivalued data corresponding to the printing characteristics of an output device such as a printer with reference to the correction data stored in a γ correction ROM 101. The error data E of the intended pixel is added to the multivalued data D' subjected to γ correction by an adder 102 of an error spread processing unit 107, so that $F = D' + E$ is output.

5 in the case where $F < Th$, a binary signal $B = "0"$ is
output. From this output result, the binarization error
 E' is calculated as $E' = F - B'$ by a subtractor 106.

10 multivalued data D is 230 and the binarization threshold value Th is 128, for example, the output data after binarization is B = 1, so that the binarization error E' is given as $E' = D - B \times 255 = 230 - 1 \times 255 = -25$.

15 memory 103 in order to distribute it among the data of
the pixels subsequently processed in accordance with a
predetermined error matrix M_{xy} in a weighted error
calculator 105, and added to the multivalued data of the
next pixel by an adder 102, thereby transmitting the
20 error data.

25 corresponding to 255 out of 256 tones. Thus, an error of
25 develops with respect to 230 of the input multivalued
data D. The error 25 with respect to the input
multivalued data D of 230 is determined as a binarization

5 The error matrix used in the conventional error
spreading method is shown in Fig. 6.

The error generated in binarizing this intended pixel is distributed to the unprocessed the next pixels with the weighting coefficients (7, 1, 5, 3) shown in Fig. 6. In binarizing the intended pixel indicated by *, the error distribution value stored is read from the error memory 103, and the next input value read from the image memory 100 is corrected using this error distribution value.

The image binarized by the error spreading method poses the problem of the reproducibility of the edge portion of the binarized image due to the fact that the error is distributed to the surrounding pixels. In other words, since the information of the surrounding pixels is partly added to the intended pixel, the

The conventional approach to this problem is a method of improving the edge retention by emphasizing the edge portion of the original multivalued data through a high-pass filter or the like.

SUMMARY OF THE INVENTION

In order to achieve this object, according to one aspect of the invention, there is provided an image processing method for generating a binary image by binarizing the pixel of the multivalued tone, comprising
20 the steps of determining an intended pixel, determining pixels adjacent to the intended pixel, determining the density difference between the intended pixel and the adjacent pixels, and setting a threshold value for the binarization of the intended pixel thereby to binarize
25 the intended pixel according to the density difference.

In the case where the density difference (edge intensity) is large between the intended pixel and the

5 Thus, the edge reproducibility of the binary image after
the error spreading process can be improved.

Fig. 1 is a block diagram showing a circuit for
executing an image processing method according to an
10 embodiment of the invention.

Figs. 3A, 3B, 3C are diagrams for explaining
15 the setting of a threshold value for the binarization
process in an image processing method according to an
embodiment of the invention.

Fig. 5 is a block diagram showing a circuit for executing the conventional error spreading method.

25 DESCRIPTION OF THE EMBODIMENTS

An embodiment of the present invention will be



This binarization error is stored in an error memory 103 for distribution to the data of the pixels subsequently processed according to a predetermined error matrix M_{xy} , added to the multivalued data of the next pixel in the adder 102, thereby transmitting the error data.

The adjacent edge detector 108 is for detecting

5

10

will be explained with reference to Fig. 2.

15

25

Now, assuming that the intended pixel is 120,
an explanation will be given of the detection as to

In the case where this value exceeds a predetermined value S, the intended pixel 120 is detected as an edge portion. In other words, in the case where the relation $DL > S$ or $DR > S$ holds, the particular

20 intended pixel is determined as an edge portion.

Although the left and right adjacent pixels of the intended pixel are assumed to be adjacent pixels in this embodiment, the density of the upper and lower adjacent pixels or all the adjacent pixels including the left and right adjacent pixels or the surrounding pixels can be referenced to improve the edge detection accuracy and perform the control operation in accordance with the edge position, thus further improving the edge

Now, an explanation will be given of the operation of controlling the dot generation upon detection of left and right adjacent edges of the intended pixel.

With the pixel of which the left or right adjacent edge has been detected, the edge retaining process is executed by controlling the dot generation in accordance with the density difference between the intended pixel and the left and right adjacent pixels. In this way, the reproducibility of the left and right adjacent edges can be improved. In controlling the dot generation, the rate of dot generation can be reduced by changing the threshold for binarization of the pixel of which left and right adjacent edges have been detected.

This process will be explained with reference to Figs. 3A to 3C showing the relation of the dot on/off with respect to the setting of the density and the threshold of the image data for the error spread operation.

Generally, the binarization threshold in the conventional error spreading method, as shown in Fig. 3A, is set and fixed at about 128 intermediate of the input density of 256 tones. According to this embodiment, on the other hand, as shown in Fig. 3B, the dot off area is widened by increasing the binarization threshold for the pixel of which left and right adjacent edges have been detected. In this way, the dot generation is suppressed

in the particular pixels so that the dot generation is reduced in the pixels adjacent to the edge thereof, thereby improving the reproducibility of the edge portion.

Also, as shown in Fig. 3C, the dot on area is widened by reducing the binarization threshold for the pixel of which right and left adjacent edges have been detected, so that the dot generation is facilitated in this pixel.

10 In this way, a more faithful edge reproduction
is made possible by changing the threshold value in
accordance with the edge intensity with the left and
right adjacent pixels of an intended pixel detected as an
edge portion.

Specifically, let D be the difference in density between the intended pixel detected as an edge portion and the left and right adjacent pixels, N be a constant for setting the variation of the threshold value, and Th be a binarization threshold for the intended pixel. Then, the threshold value is set as $Th = 128 - D/N$.

As a result, for a pixel having a large edge intensity, the binarization threshold T_h is set to a low value so that the probability of dot generation in the intended pixel increases. For a pixel having a small edge intensity, on the other hand, the binarization threshold T_h is set to a high value and therefore the probability of dot generation is decreased, with the

result that dots are not easily generated. For the pixels not determined as an edge portion, the binarization process is executed with a fixed threshold Th of 128.

5 According to this embodiment, the threshold T_h
is controlled by the aforementioned formula. A more
faithful edge reproduction is possible, however, by
controlling the threshold T_h using a formula having a
nonlinear characteristic without resorting to the formula
10 having the aforementioned linear characteristic.

Without using a calculation formula, a more detailed setting of a threshold is made possible by preparing a table for holding threshold values corresponding to the density difference D between the intended pixel and the adjacent pixels, and setting a threshold value by reference to this table.

This binarization process will be explained with reference to the flowchart of Fig. 4.

In Fig. 4, first, a line of multivalued data of the image to be binarized is stored in the image memory 100 (step s200), and then the error data distributed to the pixels on this line are stored in the error memory 103 (step s210). The density data D1 of the pixel to be binarized from a line of the data is read and a weighted error in this pixel is added thereby to acquire the intended pixel data. At the same time, this pixel data is γ -corrected based on the correction data in the γ -correction ROM 101 (step s220).

5 difference $DL = |D1 - D2|$ and $DR = |D1 - D3|$ between the density data D1 of the intended pixel and the density data D2 and D3 of the left and right pixels (step s240), respectively.

The density differences DL, DR thus obtained
10 are compared with a setting S (step s250), and in the
case where the density difference DL or DR is larger than
the setting S, the threshold determining unit 109 detects
this pixel as the one adjacent to the edge, and sets the
threshold Th using the formula $Th = 128 - D/N$ in
15 accordance with the edge intensity (step s270). In the
case where both the density differences DL and DR are
smaller than the setting S, on the other hand, this pixel
is determined as the one not adjacent to an edge and the
threshold 128 is maintained (step s260).

It is then determined whether the
aforementioned process has been completed for all the
25 pixels on the current line (step s290), and unless the
process is not complete for all the pixels of the line,
the process proceeds to the next pixel (step s310) for
executing steps s220 to s280. In the case where the

5 proceeds to the next line (step s320), and the same operation is repeated until the process for all the lines is completed.

As described above, according to this embodiment, the density difference between the intended pixel and adjacent pixels is determined, and in the case where the density difference is larger than a predetermined setting, the intended pixel is determined as an edge portion. In such a case, the threshold for binarizing the intended pixel constituting an edge portion is set to a value which is smaller, the larger the edge intensity with the adjacent pixels. As a result of this binarization, in the case where the edge intensity with the pixel adjacent to the intended pixel is large, the binarization threshold is set to a low value to increase the probability of dot generation. Otherwise, the binarization threshold is set to a high value for a lower probability of dot generation. As a result, the edge reproducibility of the binary image after the error spreading can be improved.

25 The thresholds used in this embodiment are only
an example of numerical values that can be employed, and
the invention is not limited to these numerical values.

It will thus be understood from the foregoing

[illegible]